

Model	ICE-1588D
Capacity	1.5 / 1.6 L/QT
Power consumption	250 W
Noise level	≤50 dB(A)
Product (WxDxH)	280x411x462 mm
Packing (WxDxH)	465x342x495 mm
N.W/G.W.	16.7 / 18.1 Kg
Loading (20°/40°/40°HQ)	340/688/860 pcs



A black and silver ice cream machine with two dispensing nozzles, shown next to a bowl of pink ice cream and strawberries.

Model	ICE-2410
Capacity	2.4 / 2.5 L/QT
Power consumption	250 W
Noise level	≤50 dB(A)
Product (WxDxH)	408.2x306.5x394.4 mm
Packing (WxDxH)	474x368x483 mm
N.W/G.W.	17.6 / 19.0 Kg
Loading (20°/40°/40°HQ)	308/628/785 pcs



A black and silver ice cream machine with two dispensing nozzles, shown next to a bowl of pink ice cream and strawberries.

Model	ICR-2450
Capacity	17 kg/24h
Power consumption	120 W
Noise level	≤55 dB(A)
Product (WxDxH)	381x273x245 mm
Packing (WxDxH)	447x338x288 mm
N.W/G.W.	10 / 10.9 Kg
Loading (20°/40°/40°HQ)	687/1407/1583 pcs



A white and silver ice cream machine with a single dispensing nozzle, shown next to two glasses of pink ice cream.

Model	WR-1068
Capacity	10 Kg
Power consumption	60 W
Noise level	≤45 dB(A)
Product (WxDxH)	453x218x495 mm
Packing (WxDxH)	498x270x550 mm
N.W/G.W.	6.7 / 7.7 Kg
Loading (20°/40°/40°HQ)	408/820/935 pcs



A white rice cooker with a digital display and buttons, shown next to a bowl of white rice.

Model	IYM-1501
Capacity	1.5 / 1.6 L/QT
Power consumption	55 W
Noise level	≤35 dB(A)
Product (WxDxH)	181x250x253 mm
Packing (WxDxH)	310x230x316 mm
N.W/G.W.	2.35 / 3.7 Kg
Loading (20°/40°/40°HQ)	1375/2760/3075 pcs



A white yogurt maker with a digital display and buttons, shown next to a glass of yogurt and a bowl of fruit.

Model	TR241
Capacity	24 / 0.85 Litre
Power consumption	60 W
Noise level	≤50 dB(A)
Product (WxDxH)	392.2x493.2x470.2 mm
Packing (WxDxH)	560x465x440 mm
N.W/G.W.	9.5 / 11.1 Kg
Loading (20°/40°/40°HQ)	260/525/625 pcs



A white ice cream machine with a single dispensing nozzle, shown next to a bowl of fruit.

Model	BCT-0510
Capacity	5.0 / 5.2 L/QT
Power consumption	65 W
Noise level	≤38 dB(A)
Product (WxDxH)	243x372x462 mm
Packing (WxDxH)	425x315x550 mm
N.W/G.W.	3.6 / 4.6 Kg
Loading (20°/40°/40°HQ)	545/1135/1280 pcs



A black and silver coffee machine with a single dispensing nozzle, shown next to a glass of coffee.

Model	BCT-0568
Capacity	5.0 / 5.2 L/QT
Power consumption	65 W
Noise level	≤35 dB(A)
Product (WxDxH)	272x414x472 mm
Packing (WxDxH)	450x324x440 mm
N.W/G.W.	5.7 / 6.8 Kg
Loading (20°/40°/40°HQ)	475/965/1125 pcs

Model	BCT-0558
Capacity	5.0 / 5.2 L/QT
Power consumption	65 W
Noise level	≤35 dB(A)
Product (WxDxH)	272x414x430 mm
Packing (WxDxH)	453x327x466 mm
N.W/G.W.	6.4 / 7.5 Kg
Loading (20°/40°/40°HQ)	460/930/1055 pcs

Model	BCT-0538
Capacity	5.0 / 5.2 L/QT
Power consumption	65 W
Noise level	≤35 dB(A)
Product (WxDxH)	272x414x430 mm
Packing (WxDxH)	450x324x462 mm
N.W/G.W.	6.6 / 7.7 Kg
Loading (20°/40°/40°HQ)	460/930/1055 pcs



Three different models of black and silver coffee machines with single dispensing nozzles, shown next to glasses of coffee.

Model	BCC-0568B
Capacity	5.0 / 5.2 L/QT
Power consumption	120 W
Noise level	≤50 dB(A)
Product (WxDxH)	276.7x558.2x473.2 mm
Packing (WxDxH)	530x332x458 mm
N.W/G.W.	10.9 / 12.5 Kg
Loading (20°/40°/40°HQ)	385/775/775 pcs

Model	BCC-0558B
Capacity	5.0 / 5.2 L/QT
Power consumption	120 W
Noise level	≤50 dB(A)
Product (WxDxH)	276.7x558.2x473.2 mm
Packing (WxDxH)	530x332x458 mm
N.W/G.W.	10.9 / 12.5 Kg
Loading (20°/40°/40°HQ)	385/775/775 pcs

Model	BCC-0538B
Capacity	5.0 / 5.2 L/QT
Power consumption	120 W
Noise level	≤50 dB(A)
Product (WxDxH)	276.7x558.2x473.2 mm
Packing (WxDxH)	530x332x458 mm
N.W/G.W.	10.9 / 12.5 Kg
Loading (20°/40°/40°HQ)	385/775/775 pcs



Three different models of black and silver coffee machines with single dispensing nozzles, shown next to glasses of coffee.

Model	ICM-2001
Capacity	20 / 44 kg/lb
Power consumption	150 W
Noise level	≤60 dB(A)
Product (WxDxH)	365x270x327 mm
Packing (WxDxH)	440x315x376 mm
N.W/G.W.	10.6 / 11.7 Kg
Loading (20°/40°/40°HQ)	564/1152/1335 pcs

Model	ICM-1203
Capacity	12 / 26 kg/lb
Power consumption	120 W
Noise level	≤60 dB(A)
Product (WxDxH)	244x373x315 mm
Packing (WxDxH)	440x315x376 mm
N.W/G.W.	9.5 / 10.9 Kg
Loading (20°/40°/40°HQ)	585/1190/1390 pcs

Model	ICM-2005
Capacity	20 / 44 kg/lb
Power consumption	150 W
Noise level	≤60 dB(A)
Product (WxDxH)	365x270x327 mm
Packing (WxDxH)	440x315x376 mm
N.W/G.W.	10.6 / 11.7 Kg
Loading (20°/40°/40°HQ)	564/1152/1335 pcs

Model	ICM-1206
Capacity	12 / 26 kg/lb
Power consumption	120 W
Noise level	≤60 dB(A)
Product (WxDxH)	244x373x315 mm
Packing (WxDxH)	440x315x376 mm
N.W/G.W.	9.5 / 10.9 Kg
Loading (20°/40°/40°HQ)	585/1190/1390 pcs

Model	ICM-1588
Capacity	15 / 33 kg/lb
Power consumption	150 W
Noise level	≤60 dB(A)
Product (WxDxH)	288.6x355.9x355.3 mm
Packing (WxDxH)	422x344x415 mm
N.W/G.W.	11.4 / 12.5 Kg
Loading (20°/40°/40°HQ)	465/930/1118 pcs

Model	ICM-1211
Capacity	12 / 26 kg/lb
Power consumption	120 W
Noise level	≤60 dB(A)
Product (WxDxH)	244x373x315 mm
Packing (WxDxH)	440x315x376 mm
N.W/G.W.	9.5 / 10.9 Kg
Loading (20°/40°/40°HQ)	585/1190/1390 pcs

Model	ICM-2088
Capacity	20 / 44 kg/lb
Power consumption	150 W
Noise level	≤60 dB(A)
Product (WxDxH)	288.6x355.9x355.3 mm
Packing (WxDxH)	422x344x415 mm
N.W/G.W.	11.4 / 12.5 Kg
Loading (20°/40°/40°HQ)	465/930/1118 pcs



Seven different models of ice cream machines, shown next to bowls of ice cream and glasses of coffee.



ZHONGSHAN DONLIM WEILI ELECTRICAL APPLIANCES CO.,LTD.
NO.1 DONGWEI ROAD, FUSHA INDUSTRIAL ZONE, FUSHA TOWN, ZHONGSHAN,
GUANGDONG, CHINA

Tel: +86-760-22507279
Fax: +86-760-22507078

<http://www.weili.com.cn>



Cooling Appliances Catalogue



A white and silver ice cream machine is shown on a kitchen counter, next to a vase of yellow flowers and a window with a view of greenery.



Model	ICE-1281
Capacity	1.2 / 1.3 L/QT
Power consumption	135 W
Noise level	≤55 dB(A)
Product (WxDxH)	250x275x350 mm
Packing (WxDxH)	335x305x420 mm
N.W/G.W.	9.0 / 9.8 Kg
Loading (20°/40°/40°HQ)	665/1345/1610 pcs



Model	ICE-2080
Capacity	2.0 / 2.1 L/QT
Power consumption	180 W
Noise level	≤55 dB(A)
Product (WxDxH)	272x215x362 mm
Packing (WxDxH)	380x322x422 mm
N.W/G.W.	13.0 / 13.9 Kg
Loading (20°/40°/40°HQ)	555/1125/1350 pcs



Model	ICE-2581
Capacity	2.5 / 2.6 L/QT
Power consumption	200 W
Noise level	≤55 dB(A)
Product (WxDxH)	272x315x452 mm
Packing (WxDxH)	380x322x462 mm
N.W/G.W.	14.7 / 15.7 Kg
Loading (20°/40°/40°HQ)	550/1115/1115 pcs



Model	ICE-1282Y
Capacity	1.2 / 1.3 L/QT
Power consumption	135 W
Noise level	≤55 dB(A)
Product (WxDxH)	250x275x350 mm
Packing (WxDxH)	335x305x420 mm
N.W/G.W.	9.0 / 9.8 Kg
Loading (20°/40°/40°HQ)	665/1345/1610 pcs



Model	ICE-2581
Capacity	2.5 / 2.6 L/QT
Power consumption	200 W
Noise level	≤55 dB(A)
Product (WxDxH)	272x315x452 mm
Packing (WxDxH)	380x322x462 mm
N.W/G.W.	14.7 / 15.7 Kg
Loading (20°/40°/40°HQ)	550/1115/1115 pcs



Model	ICE-2030
Capacity	2.0 / 2.1 L/QT
Power consumption	180 W
Noise level	≤55 dB(A)
Product (WxDxH)	425x285x262 mm
Packing (WxDxH)	488x345x310 mm
N.W/G.W.	11.7 / 12.6 Kg
Loading (20°/40°/40°HQ)	560/1125/1280 pcs



Model	ICE-2031
Capacity	2.0 / 2.1 L/QT
Power consumption	180 W
Noise level	≤55 dB(A)
Product (WxDxH)	425x285x262 mm
Packing (WxDxH)	488x345x310 mm
N.W/G.W.	11.7 / 12.6 Kg
Loading (20°/40°/40°HQ)	560/1125/1280 pcs



Model	ICE-2032
Capacity	2.0 / 2.1 L/QT
Power consumption	180 W
Noise level	≤55 dB(A)
Product (WxDxH)	425x285x262 mm
Packing (WxDxH)	488x345x310 mm
N.W/G.W.	11.7 / 12.6 Kg
Loading (20°/40°/40°HQ)	560/1125/1280 pcs



Model	ICE-2033
Capacity	2.0 / 2.1 L/QT
Power consumption	180 W
Noise level	≤55 dB(A)
Product (WxDxH)	425x285x262 mm
Packing (WxDxH)	488x345x310 mm
N.W/G.W.	11.7 / 12.6 Kg
Loading (20°/40°/40°HQ)	560/1125/1280 pcs



Model	ICE-2035BY
Capacity	2.0 / 2.1 L/QT
Power consumption	180 W
Noise level	≤55 dB(A)
Product (WxDxH)	425x285x262 mm
Packing (WxDxH)	488x345x310 mm
N.W/G.W.	11.7 / 12.6 Kg
Loading (20°/40°/40°HQ)	560/1125/1280 pcs



Model	ICE-2037
Capacity	2.0 / 2.1 L/QT
Power consumption	180 W
Noise level	≤55 dB(A)
Product (WxDxH)	425x285x262 mm
Packing (WxDxH)	488x345x310 mm
N.W/G.W.	11.7 / 12.6 Kg
Loading (20°/40°/40°HQ)	560/1125/1280 pcs



Model	ICE-2038
Capacity	2.0 / 2.1 L/QT
Power consumption	180 W
Noise level	≤55 dB(A)
Product (WxDxH)	425x285x262 mm
Packing (WxDxH)	488x345x310 mm
N.W/G.W.	11.7 / 12.6 Kg
Loading (20°/40°/40°HQ)	560/1125/1280 pcs



Model	ICE-1516
Capacity	1.5 / 1.6 L/QT
Power consumption	150 W
Noise level	≤55 dB(A)
Product (WxDxH)	402x281x245 mm
Packing (WxDxH)	460x338x340 mm
N.W/G.W.	10.3 / 11.3 Kg
Loading (20°/40°/40°HQ)	590/1220/1225 pcs



Model	ICE-1519
Capacity	1.5 / 1.6 L/QT
Power consumption	150 W
Noise level	≤55 dB(A)
Product (WxDxH)	402x281x245 mm
Packing (WxDxH)	460x338x340 mm
N.W/G.W.	10.3 / 11.3 Kg
Loading (20°/40°/40°HQ)	590/1220/1225 pcs



Model	ICE-1526
Capacity	1.5 / 1.6 L/QT
Power consumption	150 W
Noise level	≤55 dB(A)
Product (WxDxH)	402x281x245 mm
Packing (WxDxH)	460x338x340 mm
N.W/G.W.	10.3 / 11.4 Kg
Loading (20°/40°/40°HQ)	590/1220/1225 pcs



Model	ICE-1536
Capacity	1.5 / 1.6 L/QT
Power consumption	150 W
Noise level	≤55 dB(A)
Product (WxDxH)	402x281x245 mm
Packing (WxDxH)	460x338x340 mm
N.W/G.W.	10.3 / 11.8 Kg
Loading (20°/40°/40°HQ)	590/1220/1225 pcs



Model	ICE-1210
Capacity	1.2 / 1.3 L/QT
Power consumption	135 W
Noise level	≤55 dB(A)
Product (WxDxH)	400x260x188 mm
Packing (WxDxH)	456x316x270 mm
N.W/G.W.	9.5 / 10.1 Kg
Loading (20°/40°/40°HQ)	744/1510/1700 pcs



Model	ICE-1211
Capacity	1.2 / 1.3 L/QT
Power consumption	135 W
Noise level	≤55 dB(A)
Product (WxDxH)	400x260x188 mm
Packing (WxDxH)	456x316x270 mm
N.W/G.W.	9.5 / 10.1 Kg
Loading (20°/40°/40°HQ)	744/1510/1700 pcs



Model	ICE-1018
Capacity	1.0 / 1.0 L/QT
Power consumption	135 W
Noise level	≤50 dB(A)
Product (WxDxH)	385x285x320 mm
Packing (WxDxH)	437x337x368 mm
N.W/G.W.	9.2 / 10.0 Kg
Loading (20°/40°/40°HQ)	546/1116/1302 pcs



Model	ICE-1016
Capacity	1.0 / 1.0 L/QT
Power consumption	135 W
Noise level	≤50 dB(A)
Product (WxDxH)	385x280x289 mm
Packing (WxDxH)	418x334x324 mm
N.W/G.W.	6.2 / 6.9 Kg
Loading (20°/40°/40°HQ)	686/1372/1568 pcs



Model	KI-108
Capacity	1.0 / 1.0 L/QT
Power consumption	135 W
Noise level	≤50 dB(A)
Product (WxDxH)	388x275x322 mm
Packing (WxDxH)	444x332x372 mm
N.W/G.W.	8.8 / 9.8 Kg
Loading (20°/40°/40°HQ)	552/1121/1303 pcs



Model	KI-15
Capacity	1.5 / 1.6 L/QT
Power consumption	150 W
Noise level	≤50 dB(A)
Product (WxDxH)	385x300x313 mm
Packing (WxDxH)	444x352x356 mm
N.W/G.W.	10.2 / 11.4 Kg
Loading (20°/40°/40°HQ)	504/1032/1204 pcs