

Model 30MX67 Product (WxDxH) 318 x 448 x 124 (mm) Packing (WxDxH) 314 x 474 x 130 (mm) Weight (kg) 300 (55/70 lbs)	Model 30MX93 Product (WxDxH) 318 x 483 x 124 (mm) Packing (WxDxH) 314 x 474 x 130 (mm) Weight (kg) 300 (55/70 lbs)	Model 30UX84 Product (WxDxH) 318 x 448 x 124 (mm) Packing (WxDxH) 314 x 474 x 130 (mm) Weight (kg) 300 (55/70 lbs)
Model 30UX94 Product (WxDxH) 318 x 448 x 124 (mm) Packing (WxDxH) 314 x 474 x 130 (mm) Weight (kg) 300 (55/70 lbs)	Model 30UX97 Product (WxDxH) 318 x 448 x 124 (mm) Packing (WxDxH) 314 x 474 x 130 (mm) Weight (kg) 300 (55/70 lbs)	Model 30UX41 Product (WxDxH) 318 x 448 x 124 (mm) Packing (WxDxH) 314 x 474 x 130 (mm) Weight (kg) 300 (55/70 lbs)
Model 30UX65 Product (WxDxH) 318 x 448 x 124 (mm) Packing (WxDxH) 314 x 474 x 130 (mm) Weight (kg) 300 (55/70 lbs)	Model 30PX86 Product (WxDxH) 318 x 420 x 124 (mm) Packing (WxDxH) 314 x 474 x 130 (mm) Weight (kg) 300 (55/70 lbs)	Model 28PX94 Product (WxDxH) 284 x 448 x 124 (mm) Packing (WxDxH) 282 x 480 x 130 (mm) Weight (kg) 300 (55/70 lbs)
Model 30PX83 Product (WxDxH) 318 x 448 x 124 (mm) Packing (WxDxH) 314 x 474 x 130 (mm) Weight (kg) 300 (55/70 lbs)	Model 30PX98 Product (WxDxH) 318 x 480 x 124 (mm) Packing (WxDxH) 314 x 500 x 130 (mm) Weight (kg) 300 (55/70 lbs)	Model 30PX49 Product (WxDxH) 318 x 448 x 124 (mm) Packing (WxDxH) 314 x 474 x 130 (mm) Weight (kg) 300 (55/70 lbs)

 Model 20UX22-1 Power (Watt) 45 + 284 + 2563 (pp) Power (Watt) 470 (100 + 280) (pp) Loading (20*40*40cm)	 Model 20UX23-1 Power (Watt) 45 + 380 + 2563 (pp) Power (Watt) 470 (100 + 280) (pp) Loading (20*40*40cm)	 Model 20UX34-1 Power (Watt) 45 + 340 + 2563 (pp) Power (Watt) 470 (100 + 280) (pp) Loading (20*40*40cm)
 Model 20UX39-1 Power (Watt) 45 + 284 + 2563 (pp) Power (Watt) 470 (100 + 280) (pp) Loading (20*40*40cm)	 Model 20UX40-1 Power (Watt) 45 + 380 + 2563 (pp) Power (Watt) 470 (100 + 280) (pp) Loading (20*40*40cm)	 Model 20UX43-1 Power (Watt) 45 + 340 + 2563 (pp) Power (Watt) 470 (100 + 280) (pp) Loading (20*40*40cm)
 Model 20UX47-1 Power (Watt) 45 + 284 + 2563 (pp) Power (Watt) 470 (100 + 280) (pp) Loading (20*40*40cm)	 Model 20UX48-1 Power (Watt) 45 + 340 + 2563 (pp) Power (Watt) 470 (100 + 280) (pp) Loading (20*40*40cm)	 Model 20UX51-1 Power (Watt) 45 + 340 + 2563 (pp) Power (Watt) 470 (100 + 280) (pp) Loading (20*40*40cm)
 Model 20UX63-1 Power (Watt) 45 + 280 + 2563 (pp) Power (Watt) 470 (100 + 280) (pp) Loading (20*40*40cm)	 Model 20UX71-1 Power (Watt) 45 + 380 + 2563 (pp) Power (Watt) 470 (100 + 280) (pp) Loading (20*40*40cm)	 Model 20UX73-1 Power (Watt) 45 + 340 + 2563 (pp) Power (Watt) 470 (100 + 280) (pp) Loading (20*40*40cm)

[illegible]

Model 23M100-L Product (WxDxH) 486 x 300.5 x 320 (mm) Packing (WxDxH) 558 x 420 x 322 (mm) Loading (20" 4E 14T/15T) 410 x 560 x 940 (pcs)	Model 23M140 Product (WxDxH) 481 x 366.4 x 273.2 (mm) Packing (WxDxH) 554 x 420 x 322 (mm) Loading (20" 4E 14T/15T) 410 x 560 x 940 (pcs)	Model 23M160-L Product (WxDxH) 486 x 370.5 x 323 (mm) Packing (WxDxH) 558 x 420 x 322 (mm) Loading (20" 4E 14T/15T) 410 x 560 x 940 (pcs)
Model 23M140-P Product (WxDxH) 486 x 371 x 267.4 (mm) Packing (WxDxH) 558 x 420 x 322 (mm) Loading (20" 4E 14T/15T) 410 x 560 x 940 (pcs)	Model 23M160 Product (WxDxH) 481 x 353.2 x 273.2 (mm) Packing (WxDxH) 554 x 420 x 322 (mm) Loading (20" 4E 14T/15T) 410 x 560 x 940 (pcs)	Model 23M160-L Product (WxDxH) 486 x 370.5 x 323 (mm) Packing (WxDxH) 558 x 420 x 322 (mm) Loading (20" 4E 14T/15T) 410 x 560 x 940 (pcs)
Model 23M160-P Product (WxDxH) 486 x 371.2 x 267.4 (mm) Packing (WxDxH) 558 x 420 x 322 (mm) Loading (20" 4E 14T/15T) 410 x 560 x 940 (pcs)	Model 23M160 Product (WxDxH) 481 x 353.2 x 273.2 (mm) Packing (WxDxH) 554 x 420 x 322 (mm) Loading (20" 4E 14T/15T) 410 x 560 x 940 (pcs)	Model 23M160-L Product (WxDxH) 486 x 370.5 x 323 (mm) Packing (WxDxH) 558 x 420 x 322 (mm) Loading (20" 4E 14T/15T) 410 x 560 x 940 (pcs)
Model 23M160-P Product (WxDxH) 486 x 371.2 x 267.4 (mm) Packing (WxDxH) 558 x 420 x 322 (mm) Loading (20" 4E 14T/15T) 410 x 560 x 940 (pcs)	Model 23M160-L Product (WxDxH) 486 x 370.5 x 323 (mm) Packing (WxDxH) 558 x 420 x 322 (mm) Loading (20" 4E 14T/15T) 410 x 560 x 940 (pcs)	Model 23M160-L Product (WxDxH) 486 x 370.5 x 323 (mm) Packing (WxDxH) 558 x 420 x 322 (mm) Loading (20" 4E 14T/15T) 410 x 560 x 940 (pcs)
Model 23M160-P Product (WxDxH) 486 x 369.2 x 267.4 (mm) Packing (WxDxH) 558 x 420 x 322 (mm) Loading (20" 4E 14T/15T) 410 x 560 x 940 (pcs)	Model 23M160-L Product (WxDxH) 486 x 369.2 x 267.4 (mm) Packing (WxDxH) 558 x 420 x 322 (mm) Loading (20" 4E 14T/15T) 410 x 560 x 940 (pcs)	Model 23M160-L Product (WxDxH) 486 x 369.2 x 267.4 (mm) Packing (WxDxH) 558 x 420 x 322 (mm) Loading (20" 4E 14T/15T) 410 x 560 x 940 (pcs)

 Model 23UW16 Product (WxDxH) 483 x 390 x 173.2 (mm) Power (W) 150 (400/220 V) Loading (23°/40°/140°) 415/500/900 (kg)	 Model 23UW37 Product (WxDxH) 483 x 390 x 173.2 (mm) Power (W) 150 (400/220 V) Loading (23°/40°/140°) 415/500/900 (kg)	 Model 23UW39 Product (WxDxH) 483 x 390 x 173.2 (mm) Power (W) 150 (400/220 V) Loading (23°/40°/140°) 415/500/900 (kg)
 Model 23UW30 Product (WxDxH) 483 x 390 x 173.2 (mm) Power (W) 150 (400/220 V) Loading (23°/40°/140°) 415/500/900 (kg)	 Model 23UW68 Product (WxDxH) 483 x 390 x 173.2 (mm) Power (W) 150 (400/220 V) Loading (23°/40°/140°) 415/500/900 (kg)	 Model 23UW79 Product (WxDxH) 483 x 390 x 173.2 (mm) Power (W) 150 (400/220 V) Loading (23°/40°/140°) 415/500/900 (kg)
 Model 23UW34 Product (WxDxH) 483 x 390 x 173.2 (mm) Power (W) 150 (400/220 V) Loading (23°/40°/140°) 415/500/900 (kg)	 Model 23UW37 Product (WxDxH) 483 x 390 x 173.2 (mm) Power (W) 150 (400/220 V) Loading (23°/40°/140°) 415/500/900 (kg)	 Model 23UW69 Product (WxDxH) 483 x 390 x 173.2 (mm) Power (W) 150 (400/220 V) Loading (23°/40°/140°) 415/500/900 (kg)
 Model 23UW50 Product (WxDxH) 483 x 390 x 173.2 (mm) Power (W) 150 (400/220 V) Loading (23°/40°/140°) 380/720/915 (kg)	 Model 23PW50 Product (WxDxH) 483 x 390 x 173.2 (mm) Power (W) 150 (400/220 V) Loading (23°/40°/140°) 380/720/915 (kg)	 Model 23KX51 Product (WxDxH) 483 x 390 x 263.5 (mm) Power (W) 150 (400/220 V) Loading (23°/40°/140°) 380/720/915 (kg)